

## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6: E21B 17/08, 43/10, 43/08, F16L 13/14

(11) International Publication Number: A1

WO 98/22690

(43) International Publication Date:

28 May 1998 (28.05.98)

(21) International Application Number:

PCT/EP97/06671

(22) International Filing Date:

21 November 1997 (21.11.97)

(30) Priority Data:

96203272.8 22 November 1996 (22.11.96) EP (34) Countries for which the regional or international application was filed:

GB et al.

(71) Applicant (for all designated States except CA): SHELL INTERNATIONALE RESEARCH MAATSCHAPPU B.V. (NL/NL); Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL).

(71) Applicant (for CA only): SHELL CANADA LIMITED [CA/CA]; 400 - 4th Avenue, S.W., Calgary, Alberta T2P 2H5 (CA).

(72) Inventor: LOHBECK, Wilhelmus, Christianus, Maria; Volmeriaan 6, NL-2288 GD Rijswijk (NL).


(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, IP, KE, KG, KP, KR, KZ, LC, LK, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

#### Published

With international search report.

Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.

(54) Title: CONNECTOR FOR AN EXPANDABLE TUBING STRING



(57) Abstract

Æ

A connector for interconnecting a pair of adjacent sections (8 and 9) of an expandable tubing string comprises a plastically expandable sleeve (6) that is arranged co-axially around or inside the ends (7) of the interconnected tubing sections (8 and 9) and a series of circumferentially spaced mechanical fasteners (5), such as screws or rivets, for fastening the sleeve to each of said ends (7).

### FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

l							
AL	Albania	ES	Spain	LS	Leaotho	SI	Slovenia
AM	Amesia	PI	Pinland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	Prance	w	Luxemboure	SN	
AU	Australia	GA	Gabos	LV	Latvia	SZ.	Senegal
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Swaziland
BA	Bosnia and Herzegovina	CE	Georgia	MD	Republic of Moldova		Chad
88	Barbados	GH	Ghasa	MG	Madagascar	TG	Togo
BE	Belgium	GN	Guinea	MK	The former Yugoslav	ŢĴ	Tajikistan
BY	Burkins Paso	GR	Greece	<i>_</i>	Republic of Macedonia	TM	Terkmenistan
BG	Bulgaria	HU	Hongary	ML	Mali	TR	Turkey
BJ	Benin	(B	Ireland	MN		TT	Trinidad and Tobago
BR	Brazil	(L	Israel	MR	Mongolia	UA	Ukraine
BY	Belarus	15	Iceland	MW	Mauritania	UG	Uganda
CA	Canada	iī	haly	MX	Malawi	US	United States of America
CP	Central African Republic	JP	Japan	NE NE	Mexico	UZ.	Uzbekistan
CG	Congo	KE	Konya		Niger	VN	Vict Nam
CH	Switzerland	KG		NL	Netherlands	YU	Yugoslavia
a	Côte d'Ivoire	KP	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CM	Cameroon	M.F	Democratic People's	NZ	New Zealand		
CN	China	***	Republic of Korea	PL	Poland		
Ċυ	Cuba	KR	Republic of Korea	PT	Portegal		
cz		KZ.	Karakstan	RO	Romania		
	Czech Republic	LC	Saint Lucia	RU	Russian Foderation		
DE	Germany	u	Liechteastein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
Œ	Estonia	LR	Liberia	8G	Singapore		

10

15

20

25

## CONNECTOR FOR AN EXPANDABLE TUBING STRING

The invention relates to a connector for use in connecting sections of an expandable tubing string, and in particular but not exclusively for use in the connection of sections of an expandable slotted tubing (EST) string as utilized in downhole applications in oil and gas production operations.

Expandable slotted tubings are known from International patent application No. PCT/EP 93/01460. This prior art reference discloses a slotted tube which may be expanded downhole by running an expansion mandrel through the tubing whereby the slots are expanded to diamond-shaped apertures.

When a tubing is expanded it is desirable that this can be accomplished by a substantially uniform expansion force, also at the locations where adjacent tubing sections are interconnected.

It is therefore an object of the present invention to provide a connector for an expandable tubing that can be expanded smoothly and made up easily without requiring welding operations.

The connector according to the invention thereto comprises a plastically expandable sleeve that is in use arranged co-axially relative to an end of each of the adjacent tubing sections, and means for fastening the sleeve to said ends.

Preferably the outer surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.

10

15

20

25

30

Alternatively the inner surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.

It is preferred that the thickness of the sleeve is substantially equal to the depth of the annular recess so that a flush-type connection is created.

It is furthermore preferred that the fastening means comprise a series of circumferentially spaced screws that pass through holes that are drilled through the sleeve and the adjacent wall of ends of the adjacent tubing sections. If desired the screws may be replaced by rivets or other mechanical fasteners.

The connector according to the invention is particularly attractive for interconnecting sections of an expandanble string of oil and/or gas well tubulars that may be slotted. If the connector is used for interconnecting sections of an expandable slotted tubing string then the sleeve is provided with a series of staggered substantially longitudinal slots which are deformable into diamond-shaped apertures upon expansion of the sleeve.

Further aspects, details, objects and advantages of the connector according to the invention will become apparent from the accompanying claims, abstract, drawings and detailed description with reference to the drawings.

The invention will now be described in more detail with reference to the accompanying drawings, in which

Fig. 1 shows a schematic side view of a plastically expandable connector according to the invention which surrounds ends of adjacent expandable slotted tubing sections;

WO 98/22690 PCT/EP97/06671

- 3 -

Fig. 2 shows a schematic longitudinal sectional view of a flush-type connector according to the invention which surrounds ends of adjacent expandable tubing sections; and

Fig. 3 shows a schematic longitudinal sectional view of a flush-type connector according to the invention which is surrounded by ends of adjacent expandable tubing sections.

5

10

15

20

25

30

4

Referring now to Fig. 1, there is shown a connector comprising a plastically deformable slotted sleeve 1 that co-axially surrounds ends of a pair of adjacent slotted tubing sections 2 and 3. The sleeve 1 and tubing sections are each provided with a series of staggered and partially overlapping slots 4 that deform to substantially diamond shaped apertures (not shown) upon expansion of the assembly by e.g. running an expansion mandrel (not shown) through the interior of the tubing sections 2 and 3.

One or more series of circumferentially spaced Allen-type or other locking screws 5 fasten the sleeve 1 to each of the tubing sections 2 and 3 such that the inner surface of the sleeve 1 engages the outer surface of the end of each tubing section 2 and 3 both before, during and after the expansion process. The screws 5 are located in nodes between slots 4.

Referring now to Fig. 2 there is shown a flush-type connector comprising a plastically deformable solid or slotted sleeve 6 that surrounds ends 7 of adjacent solid or slotted tubing sections 8 and 9, which ends 7 have been machined away to form an annular recess 10 in which the sleeve 6 is located. The thickness of the sleeve 6 substantially equals the depth of the recess 10 to form a flush-type connector.

WO 98/22690 PCT/EP97/06671

- 4 -

The connector furthermore comprises a series of circumferentially spaced Allen-type or other locking screws 11 to fasten the sleeve 6 to each of the tubing sections 8 and 9 such that the inner surface of the sleeve 6 engages the outer surface of the ends 7 of the adjacent tubing sections 8 and 9 both before, during and after the expansion process.

5

10

15

20

25

4

Referring now to Figure 3 there is shown a flush-type connector comprising a plastically deformable solid or slotted sleeve 16 that is surrounded by ends 17 of adjacent solid or slotted tubing sections 18 and 19, respectively, which ends 17 have been machined away to form an annular recess 20 in which the sleeve 16 is located. The thickness of the sleeve substantially equals the depth of the recess 20 to form a flush-type connector that smoothly deforms plastically together with the ends of the tubing sections 18 and 19 during the expansion process.

The connector of Fig. 3 furthermore comprises a series of circumferentially spaced Allen-type locking screws 21 to fasten the sleeve 16 to each of the tubing sections 18 and 19 such that the outer surface of the sleeve 16 firmly engages the inner surface of the ends 17 of the adjacent tubing sections 8 and 9 both before, during and after the expansion process.

20

#### CLAIMS

- 1. A connector for interconnecting adjacent sections of a tubing string, the connector comprising a sleeve that is in use arranged co-axially relative to an end of each of the adjacent tubing sections, and means for fastening the sleeve to said ends, characterized in that the sleeve is plastically expandable and is useable for interconnecting sections of an expandable tubing string.
- 2. The connector of claim 1, wherein the sleeve is designed for interconnecting sections of an expandable slotted tubing string and is provided with a series of staggered substantially longitudinal slots which are deformable into diamond-shaped apertures upon expansion of the sleeve.
- 3. The connector of claim 1, wherein the sleeve is designed for interconnecting sections of an expandable string of oil and/or gas well tubulars.
  - 4. The connector of claim 1, wherein the outer surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which the sleeve is located.
  - 5. The connector of claim 1, wherein the inner surface of an end of each of the adjacent tubing sections has been machined away to form an annular recess in which
- 25 the sleeve is located.
  - 6. The connector of claim 4 or 5, wherein the thickness of the sleeve is substantially equal to the depth of the annular recess.

7. The connector of any preceding claim, wherein the fastening means comprise a series of circumferentially spaced screws that pass through holes that are drilled through the sleeve and the adjacent wall of ends of the adjacent tubing sections.




FIG.2





FIG.3



Inte .ional Application No PCT/EP 97/06671

A. CLASS IPC 6	FICATION OF SUBJECT MATTER E21B17/08 E21B43/10 E21B43/	08 F16L13/14	
According t	o International Patent Classification (IPC) or to both national classific	ation and IPC	
	SEARCHED		
Minimum a IPC 6	ocumentation searched (classification system followed by classificati E21B F16L	on symbols)	***************************************
Documenta	ition searched other than minimum documentation to the exient that e	uch documents are included in the fields se	arched
Electronic o	tata base consulted during the international search (name of data ba	se and, where practical, search terms used	)
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the rel	ovant passages	Relevant to claim No.
X	US 3 948 321 A (OWEN) 6 April 19 see column 5, line 13 - line 50 see column 7, line 37 - line 41	76	1,3-6
Y			2
Y	US 5 366 012 A (LOHBECK) 22 Nover cited in the application see the whole document	mber 1994	2
X	US 3 863 959 A (BLASCHKE) 4 Febru see abstract	uary 1975	1,3-7
X	DE 24 34 298 A (HERMANN VON RAUTE INTERNATIONALE TIEFBOHR KG ITAG) January 1976 see page 4, line 9 - page 5, line	1,3-7	
	<del></del>	-/	
X Furth	ner documents are listed in the continuation of box C.	Patent family members are fisted in	in annex.
Special ca	legories of cited documents;		
consid	ork defining the general state of the art which is not ered to be of particular relevance locument but published on or after the international	"I" later document published after the Inter or priority date and not in conflict with cited to understand the principle or the invention	the application but early underlying the
filing d L" docume which	ate nt which may throw doubts on priority claim(s) or is cited to establish the publication date of another no other special reason (as specified)	"X" document of particular relevance; the c cannot be considered novel or cannot involve an inventive step when the do "Y" document of particular relevance; the c	the considered to current is taken alone
O" docume other r P" docume	ent referring to an oral disclosure, use, exhibition or neane int published prior to the international filing date but	cannot be considered to involve an in- document is combined with one or mo ments, such combination being obvior in the art.	ventive step when the ore other such docu-
later th	an the priority date claimed scrual completion of theinternational search	"&" document member of the same patent  Date of mailing of the international sea	
24	4 March 1998	30/03/1998	
Vame and n	nailing address of the ISA  European Patent Office, P.B. 5618 Patentiaan 2  Mil. 2200 MV Ottouth	Authorized officer	
	NL - 2200 HV Piljswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl. Fav. (+31-70) 340-2016	Soano M	

Form PCT/ISA/210 (second sheet) (Adv 1982

1

Inte. Jonal Application No PCT/EP 97/06671

ategory '	ation) DOCUMENTS CONSIDERED TO BE RELEVANT  Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
(	WO 95 25239 A (ATLAS COPCO GEOTECHNICAL DRILLING AB) 21 September 1995 see abstract	1,3-5
(	US 2 871 034 A (WILTSE) 27 January 1959 see column 1, line 59 - column 2, line 4	1,3,5,6
(	GB 792 886 A (HUNTSINGER) 2 April 1958 see page 3, line 116 - line 124; figures 4,9,11	1,3,4,7
(	US 3 585 803 A (BARDGETTE) 22 June 1971 see column 2, line 71 - column 3, line 1	1,3,4,7
(	DE 90 13 606 U (BRM GMBH) 31 October 1991 see the whole document	1,3,7
(	FR 1 565 562 A (RABUEL) 2 May 1969 see page 2, left-hand column, line 10 - right-hand column, line 4	1,3
(	DE 41 33 802 C (HAWERKAMP) 22 October 1992 see the whole document	1,3
(	WO 93 14284 A (WELAND AB) 22 July 1993 see page 4, line 4 - line 6 see page 5, line 6 - line 21	1,7
,	DE 295 18 333 U (NOVOPRESS GMBH) 11 January 1996 see page 5, line 21 - line 26; figure 2	1
	EP 0 611 614 A (B & W FUEL COMPANY) 24 August 1994 see abstract	1
	DE 43 29 442 A (DEUTSCHE ALWA GMBH) 2 March 1995 see abstract	1
, <b>x</b>	WO 96 37680 A (SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ) 28 November 1996 see example 1 see page 2, line 23 - line 28 see page 3, line 19 - line 25 see page 4, line 14 - line 17	1-7
,х	WO 96 37681 A (PETROLINE WIRELINE SERVICES LIMITED) 28 November 1996 see the whole document	1-7
	-/	

1

iŁ.

Information on patent family members

Int. .tional Application No PCT/EP 97/06671

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 3948321 A	06-04-76	NONE	
US 5366012 A	22-11-94	AU 672008 B AU 4324593 A CA 2137565 A DE 69305852 D DE 69305852 T WO 9325800 A EP 0643795 A	19-09-96 04-01-94 23-12-93 12-12-96 22-05-97 23-12-93 22-03-95
		JP 7507611 T MD 960219 A NO 944746 A NZ 253125 A	24-08-95 31-05-97 03-02-95 27-02-96
US 3863959 A	04-02-75	CH 558872 A DE 2210980 A FR 2175229 A GB 1365657 A JP 48101614 A	14-02-75 23-08-73 19-10-73 04-09-74 21-12-73
DE 2434298 A	29-01-76	NONE	
WO 9525239 A	21-09-95	SE 503459 C AU 680753 B AU 2089095 A EP 0757768 A FI 963641 A NO 963833 A SE 9400867 A	17-06-96 07-08-97 03-10-95 12-02-97 08-11-96 25-10-96 16-09-95
US 2871034 A	27-01-59	NONE	
GB 792886 A		NONE	· *
US 3585803 A	22-06-71	NONE	
DE 9013606 U	31-10-91	NONE	
FR 1565562 A	02-05-69	NONE	

iL

Int. .tional Application No PCT/EP 97/06671

C-(Continue	NION) DOCUMENTS CONSIDERED TO BE RELEVANT	FC1/EF 9//000/1
Category *	Citation of document, with indication,where appropriate, of the relevant passages	Relevant to claim No.
(,P	WO 97 41377 A (B.D.KENDLE ENGINEERINGLIMITED ) 6 November 1997 see page 13, line 6 - line 9; figure 15 see page 7, line 19 - line 21; figure 6 see page 10, line 1 - line 3	1,3-6

1

Information on patent family members

PCT/EP 97/06671

	atent document d in search repo		Publication date	Patent famili member(s)		Publication date
DE	4133802	С	22-10-92	NONE		
WO	9314284	Α	22-07-93	SE 500185	5 C	02-05-94
				AT 154964	I T	15-07-97
				DE 69220677	7 D	07-08-97
				DE 69220677	7 T	15-01-98
				EP 0624219	) A	17-11-94
				FI 943449		20-07-94
				NO 942659		15-07-92
				SE 9200179	) A	22-07-93
DE	29518333	U	11-01-96	NONE		
EP	611614	A	24-08-94	WO 9419125	5 A	01-09-94
0E	4329442	A	02-03-95	NONE		
WO	9637680	Α	28-11-96	AU 5826596		11-12-96
				AU 7349396		11-12-96
				EP 0828918	3 A	18-03-98
				EP 0824628	3 A	25-02-98
				WO 9637681		28-11 <b>-</b> 96
				NO 975350	) A	16-01-98
WO	9637681	Α	28-11-96	AU 5826596	5 A	11-12-96
				AU 7349396		11-12-96
				WO 9637680		28-11-96
				EP 0828918		18-03-98
				EP 0824628		25-02-98
				NO 975350	) A	16-01-98
WO	9741377	Α	06-11-97	AU 2647497	' A	19-11-97